

METS 系列 規格索引

滑台電動缸-螺桿驅動 (不附馬達)



METS 滑台電動缸：

使用環境	傳動方式	型號	馬達尺寸 (W)	本體寬幅 (mm)	位置重複精度 (mm)	螺桿規格(C7級)		最大可搬重量(kg)		最高速度※1 (mm/s)					
						外徑 (mm)	導程 (mm)	水平使用 (mm)	垂直使用 (mm)						
一般環境	滾珠螺桿	METS-5M	42M (步進馬達)	51	±0.01	12	2	10	7	16					
							5	10	3	41					
							10	5	1.5	83					
			100W	51	±0.01	12	2	10	7	100					
							5	10	3	250					
							10	5	1.5	500					
		METS-6M	57M (步進馬達)	65	±0.01	12	2	30	15	16					
							5	30	10	41					
							10	15	5	83					
			100W	65	±0.01	12	2	30	15	100					
							5	30	10	250					
							10	15	5	500					
		METS-10	100W	102	±0.01	16	5	50	12	250					
							10	30	8	500					
							16	22	5	800					
							20	18	3	1000					
		METS-12	100W	102	±0.01	16	5	50	12	250					
							10	30	8	500					
							16	22	5	800					
							20	18	3	1000					
		METS-13	200W	135	±0.01	16	5	70	17	250					
							10	47	12	500					
							16	30	6	800					
							20	24	4	1000					
							METS-14	200W	135	±0.01	16	5	95	27	250
												10	75	18	500
		16	44	7	800										
		20	35	6	1000										
		METS-14	400W	135	±0.01	16	5	110	33	250					
							10	88	22	500					
							16	48	10	800					
							20	40	8	1000					
METS-17	400W						170	±0.01	20	5	120	40	250		
										10	110	30	500		
		20	75	14	1000										
		40	35	7	2000										
	750W	170	±0.01	20	5	120	50	250							
					10	120	40	500							
20					83	25	1000								
40					50	10	2000								
METS-22	750W	220	±0.01	25	5	150	55	250							
					10	150	45	500							
					25	120	20	1250							
					40	60	10	2000							

※1. 最高速度(mm/s)是以伺服馬達最高轉速3000rpm為基準，步進馬達最高轉速500rpm為基準。

